



Inner beam	Center beam	Chassis	H-16200	Suspension	Client	P-2428	Drilling hole	P-2425, 2426, 2428, H-2328
Extensions	Extensions	Inner beam	K-14907	Axle	Client	GHM/2X11 12010 Protec	Side rail	(7) 258x1140 c. (8) 140x240 c.
800	375	1st Center beam	K-14908	Raise/lower		+ 125 / - 104 mm	Stake pockets	SE-65x6
1000	750	2nd Center beam	-	Type		245/70 R17.5 HTE2	Deck	28mm Hardwood 8/10mm Checker plate
2000	1500	Outer beam	K-14905	17th axial load		Max. 35,000 kg	Spindles	K-13200
3000	1500	Special beam	-	Single load		Max. 24,000 kg	Draw holes	ø15
4000		In	H-17480	Landing gear		Just Mast B	Type vehicle	74850-95
5000		stages	P-7221	Client		Auto raise/lower valve	Chassis number	24/78-0281040103
6000		of	H-14005					
7000	800	Steering	H-14005					
8000	up to			Specification modification Drawn: M/20 Dimensions in mm Date: 20-02-2010 Scale: 1:20 Order no.: 1001030 Format: A1 Preceded 04038 Tolerances: ISO 2768-CL				
9000	9000							
10000	10100			Drawing no.: 1001030 Checked: 1001030				
Construction notes				K-14217				